



20W to 50W  
AWMA-2000C® series



### Features

- Remote Monitor & Control
- High gain and linearity
- Output power up to 50W (see table A)
- Gain adjustment
- Output sample monitor port
- Temperature gain compensation
- Automatic over-temperature shutdown
- Automatic high reflected power shutdown
- Infinite VSWR protection
- CE Marking

### Overview

The AWMA-C series are the outdoor solid-state power amplifiers (SSPAs), operating in C-Band frequency range. The amplifier is an integrated unit, complete with power supply and cooling system. Intended for outdoor operation, the AWMA-2000C® is weatherproof. Built-in microprocessor controller provides the capability for serial port interfaces (RS485) for remote monitoring and control.

Advantech's SSPAs set the industry standard for linearity and operating efficiency. Built-in design features and assembly methods incorporated with efficient combining techniques result in the trouble-free operation of the amplifier.


### Application

The SSPAs are designed for C-Band satellite up-link applications. They are mounted outdoors, near the hub of an antenna. The AWMA-C series are available in output power from 20W to 1000W. For higher power Advantech provides phase-combined systems.

Other SSPAs are available for operation at other satellite frequency bands. With all the features of the AWMA-C, Advantech also offers a built-in converter.

### Redundancy

With the addition of the appropriate waveguide and switch kit, the AWMA-2000C® amplifiers can be easily converted for the operation in 1:1 redundant configuration without the use of any external controller. Full remote Monitor and Control of the redundant system is accessible via the serial port (RS-485).



**Table A**

Band*	RF Band (GHz)	Output Power (W)
CL	4.400 - 5.000	20 - 50
CP	6.425 - 6.725	20 - 50
CI	6.725 - 7.025	20 - 50
CR	5.725 - 6.025	20 - 50
CS	5.850 - 6.425	20 - 50
CX	5.850 - 6.725	20 - 50

\*Other frequency sub-bands are available. Please consult factory.

### Options

- Integrated Block Up Converter
- Additional harmonic filter
- Extreme temperature operation
- Redundant system

### Accessories

- Redundancy Kit
- Mounting Frames
- Remote M&C panel (Ethernet port optional)

# C-Band Hub-mount SSPA/SSPB

Technical Specifications	20 W	25 W	30 W	40 W	50 W	
<b>Electrical Characteristics</b>						
Availability in this series						
CS, CR, CL, CX, CI, CP	√	√	√	√	√	
Output power (P <sub>SAT</sub> )	+43 dBm	+44 dBm	+45 dBm	+46 dBm	+47 dBm	
Output power (P1dB) min	+42 dBm	+43 dBm	+44 dBm	+45 dBm	+46 dBm	
Power gain @ maximum gain setting	56 dB min					
Operating frequency range	See table A on front page					
Max input power without damage	+10 dBm					
Gain slope	0.6 dB max over 40 MHz					
Gain flatness over 600 MHz	±1.0 dB					
Gain variation over temperature	±1.5 dB over full operating temperature range					
Gain variation over 24 hours	±0.25 dB max @ constant temperature & drive level					
Gain adjustment range	20 dB (0.1 dB resolution)					
Input return loss	18 dB					
Output return loss	19 dB					
Noise power density	-70dBm/Hz max in TX band -150 dBm/Hz max in 3.4- 4.2 GHz RX band					
Spurious at rated power	-65 dBc, max					
Harmonics at rated power	-60 dBc, max					
AM/PM conversion at rated power	2.5°/dB max. at P1dB, 1°/dB max. at 3 dB back-off					
Third order IMD (2 tones 5 MHz apart)	-26 dBc max. at 3 dB total back-off from rated P1dB					
Group delay	Linear: 0.02 nsec/MHz max. Parabolic: 0.003 nsec/MHz <sup>2</sup> max. Ripple: 1.0 nsec p-p max.					
Residual AM (F* - frequency in kHz)	0-10 kHz -45 dBc 10 kHz - 500 kHz -20 (1.25+log F*) dBc 500 kHz - 1 MHz -80 dBc					
<b>Power Requirements</b>						
AC input voltage	110/220 VAC auto ranging (47-63 Hz)					
Power consumption (nominal)	200W	250W	315W	370W	430W	
<b>Mechanical Characteristics</b>						
Dimensions (L x W x H)	16.15" x 9.75" x 9.16" (41.02 x 24.77 x 23.27 cm)					
Weight	25 Kg (55 lbs)					
Interfaces:	RF input Output sample port AC Line	Type N (Female) Type N (Female) MS3102R16-10P	Redundancy Discrete port RS-485	MS3112E14-12P MS3112E16-26P MS3112E10-6P	RF output: CPR137 contact (for CL series –CPR187)	
<b>Environmental Conditions</b>						
Temperature:	Operating Storage	-30°C to +55°C; Option: 1: -40°C to +55°C; 2: -50°C to +50°C -55°C to +85°C				
Humidity	100%, condensing (2" rain/hour)					
Altitude	10,000' AMSL, de-rated 2°C/1,000' from AMSL					

**NORTH AMERICA**  
USA  
Tel: +1 678 889-1831  
Fax: +1 678 889-1756  
info.usa@advantechwireless.com

**CANADA**  
Tel: +1 514 420 0045  
Fax: +1 514 420 0073  
info.canada@advantechwireless.com

**EUROPE**  
UNITED KINGDOM  
Tel: +44 1480 357 600  
Fax: +44 1480 357 601  
info.uk@advantechwireless.com

**RUSSIA & CIS**  
Tel: +7 495 971 59 18  
info.russia@advantechwireless.com

**SOUTH AMERICA**  
USA  
Tel: +1 678 889-1831  
Fax: +1 678 889-1756  
info.latam@advantechwireless.com

**BRAZIL**  
Tel: +55 11 3054 5701  
Fax: +55 11 3054 5701  
info.brazil@advantechwireless.com

An ISO 9001 : 2008 Company



Ref.: PB-AWMA-C-20-50-12106